



## 15 inch touch screen

LCD Panel Type	15.1 TFT LCD panel (optional)
Max. Resolution	1024(horizontal)*768(vertical)*GA
Body size	348*(W)*285(H)*55(D)mm
Contrast	400:1
Brightness	300CD/m <sup>2</sup>
Response Time	8MS
Viewing Angle left/right	+80° ~-80° or +60° ~-60°
Viewing Angle up/down	+80° ~-80° or +55° ~-65°
Enter message Visual message	RGB analog 0.7V p-p
Synchronization	TTL Anode or Cathode
Display Mode	VGA,SVGA,XGA
Signal Connector	15-hole mini D-Block
Front Panel control buttons	Power control switch, LED indicator, OSO menu, +/- adjustment button, screen automatically set, OSO choose.
OSD Adjustment	Contrast, brightness, auto adjust, image-bit quasi, phase, Horizontal position, vertical position , enter message, Computer VGA
Power Transformer	AC:100-240V~1.8A 50-60Hz DC: 12V/2.5A
Operating Environment	Temperature:0-50℃, Humidity 20-81-0%
Storage Environment	Temperature:-20-60℃, Humidity 20-81-0%
Safety Certification	FCC(DOC),CE,VCC-I,TUV/GS,TCO'99 (optional)